

Tekniset tiedot

Eromat TYYPPI 6B

OMINAISUUDET		
Kuitu	Kookos	
Kuitupitoisuus	100%	
Kokonaispaino	~ 550 g/m² +/- 10%	
Paino / Kuitu	~ 450 g/m²	
Toiminnallinen kestoikä	9-12 kuukautta	
Päällysverkon tyyppi	Luonnollinen	
Pohjaverkon tyyppi	Luonnollinen	
Päällysverkon aukkoko	8x9	
Pohjaverkon aukkoko	8x9	
Päällysverkon paino	55 g/m²	
Pohjaverkon koko	55 g/m²	
Ompelulanka	Luonnollinen	
Ompelulangan vetolujuus	13,5 cN / tex +/- 10%	
Murtovenymä	n. 2 % +/- 20%	
STANDARDIT		
ISO 10319 Vetolujuus	324,6 N / 8 cm poikittaissuunnassa 379,8 N / 8 cm konesuunnassa	
D4595 Murtovenymä (%)	34 x 20	
D4491 Virtausnopeus, lyhytaikainen	4,26 m/s	
Suurin sallittu leikkausjännitys	1100 g/m²	
„n“ value Roughness Coefficient	0,014	
TOIMITUSKOOT		
Part No.	O6B120	O6B240
Leveys	1,20 m	2,40 m
Pituus	42 m	42 m
Neliöt per rulla	50,4 m²	100,8 m²
Paino per rulla	28 kg	56 kg
Rullan halkaisija	0,40 m	0,40 m
Rullan tilavuus	0,19 m³	0,38 m³

The specifications presented herein are to the best of our knowledge true and accurate. GREENFIX cannot guarantee or warranty our products, unless agreed to in writing for specific conditions, for performance since the manner of handling; use and installation are beyond our control.

We cannot warrant our products to perform under unlimited circumstances due variables such as soil conditions, manner of installation and particularly severe weather conditions. Satisfactory results may not meet your expectations. No one can guarantee that required moisture will occur to permit growth after seed germination. We will not be liable for damages or losses, direct or indirect, of our GREENFIX Range of Products due to the above reasons.

Latest-Update: May 8, 2017

Name: Kai Tietjen

File Name: ERO 6B

Copyright of these GREENFIX Document is reserved by SOILTEC GmbH. Copying or transmission of these document in whole or in part or any information contained therein is strictly prohibited without the prior authorization of SOILTEC GmbH, Germany.