


SYSTEM DATA SHEET

“SEDUM CARPET” WITH FLORASET® FS 50



SYSTEM BUILD-UP

Sedum cuttings or plug plants according to plant list “Sedum Carpet”
System Substrate “Sedum Carpet” ca. 60 mm
Filter Sheet SF

Floraset® FS 50
Protection Mat TSM 32

Roof construction with root resistant waterproofing

DESCRIPTION/COMMENTS:

- Proven simple green roof build-up requiring only little maintenance, especially suitable for roofs with low design demands.
- Can be used on roofs with no severe ponding up to a slope of about 8°.
- Environmental protection layer instead of gravel.
- The plant layer can be realized either with Sedum cuttings or with plug plants.
- The filter-stable drainage layer exceeds the requirements of German Standard DIN 4095.
- The build-up is resistant against flying sparks and is considered to be a “hard roof” providing fire protection in accordance to German Standard DIN 4102, part 7.
- The fall protection device “Fallnet®” can be integrated into the build-up (an increase of substrate depth above the grid elements might be necessary).
- Please note: the build-up described above is suitable for the moderate continental climate of Central Europe. For information on possible adaptations for other climates please contact the Zinco Technical Department.
- If waterproofing is not root resistant an additional root barrier is required: Root Barrier WSF 40
- The indicated weights do not include the weight of the vegetation, see [Info Sheet Green Roof Ballast](#).

Zinco GmbH

Lise-Meitner-Strasse 2 | 72622 Nuertingen | Germany
Phone +49 7022 6003-0 | info@zinco-greenroof.com | www.zinco-greenroof.com

Subject to technical alterations and printing errors • First edition 12/2012; Revised 10/2024

